



Healthy People

## APPLICATION FOR ABANDONMENT OF SUBSURFACE SEWAGE DISPOSALSYSTEM COMPONENTS

240 Stafford Avenue, Bristol, Connecticut 06010-4617

Tel. (860) 584-7682 • Fax (860) 584-3814 • www.bbhd.org

**SUBMIT** site plan or sketch drawn to scale (Example 1 inch = 20 feet) with this application. Plan must show property lines, house location, septic tank, leaching system Plan must show distance from well or public water line to the proposed location of public sewer lateral.

According to the Technical Standards for Subsurface Sewage Disposal Systems (Revised January 1, 2023), Section II. F. Abandonment of any hollow SSDS component (e.g., septic tank, pump chamber, leaching chamber) or cesspool shall be performed in a manner to eliminate the danger of an inadvertent collapse. It is the property owner's responsibility to make arrangement for abandonment of any hollow SSDS component or cesspool. Hollow structures shall be emptied of all septage prior to abandonment. Structures shall be filled with sand, gravel, or other DOH approved material (e.g., concrete), crushed in place, or removed from the site for disposal as approved by the DOH. The DOH may authorize a former sewage system component (except steel tanks or cesspools) in compliance with Table 1 to be utilized for another purpose (e.g., water treatment wastewater dispersal system) rather than be formally abandoned if the property owner demonstrates the component is in acceptable condition and such use will not cause a health hazard or nuisance condition. Structures left in place shall be located on a plot plan and noted in the property file.

Abandonment Date:	Fee: \$50
il	Cesspool
upon completion of work	
Signature	
For Office Use Only    Application #: Application fee paid    Notes:	Date Inspected
	il